
Power Built™ 17.5 Gross HP

500 CC

Bore 3.56 in. (90.5 mm) Stroke 3.06 in. (77.6 mm) Oil Capacity 48 fl. oz. (1.4 L)




8.61" 6.18 (157.06)(218.67)12.21" (310.06)12.90" (327.65)7.88 **END** (200.25)VIEW



Features:

- Dura-Bore™ cast iron cylinder sleeve for extended life
- Float carburetor for consistent easy starting
- **Maintenance-free Magnetron®** electronic ignition for quick, dependable starts
- Dual-Clean™ air cleaner pleated paper filter with a foam pre-cleaner ensures maximum protection for extended engine life
- Overhead valve design (OHV) for cooler operation and longer valve life
- · Patented linear balancing system provides smoother performance
- Buyer protection package provides two-year consumer engine warranty



Model Type	Shipping Weight	Crankshaft	Crankshaft (P.T.O.) Extension	Dimension	Starter Position Bolt-On/Changeable	Ext. Oil Fill & Dipstick	Governor	Controls	Pulse Fuel Pump	Oil Pump with Filter	Choke-A-Matic®	Ground Wire Terminal	Fuel Tank (Quarts)	Top Governor Speed	Notes
31C707															
0005	82	697127	Tapped 7/16-20, Keyway, 1" dia.	3-5/32(b)	6	Х	М	R			Χ	Х		3300	▼
0026	81	697127	Tapped 7/16-20, Keyway, 1" dia.	3-5/32(b)		Х	M	R			Χ	Χ		3300	▼

■ Fuel tank omitted. ▼ Engine equipped with 12 Volt Gear Drive Starter and 9 Amp DC Alternator.